

IN THE CLAIMS:

Please amend the claims as follows:

1. (currently amended) A process for sterilizing objects on their surfaces, comprising the steps of:

dampening the object surfaces dampened by condensing a steam compound of water and hydrogen peroxide, ~~whereby the~~ and
removing the condensed condensation fluid ~~is subsequently removed from~~
the surfaces by drying,

wherein the dampening step includes abruptly releasing by condensation
~~of the steam compound into a sterilizing chamber is carried out~~ without
additional transport gas flow, so that the steam compound becomes over-
saturated and condenses in the shortest possible time on the surfaces, and

wherein the drying is carried out by evacuation at a pressure below boiling
points of water and hydrogen peroxide.

2. (cancelled)

3. A process according to claim 1, wherein the steam compound is
generated in an evaporator and subsequently fed into a separate sterilization
chamber to dampen the objects, the pressure of the sterilization chamber being
lower than the steam pressure of the steam compound.

4. A process according to claim 3, wherein the steam compound flows from the evaporator into the sterilization chamber essentially by means of adiabatic expansion.

5. (cancelled)

6. A process according to claim 1, wherein the dampening by means of condensation as well as the subsequent drying of the condensation fluid is repeated at least once.

7. (cancelled)

8. A process according to claim 3, wherein the dampening by means of condensation as well as the subsequent drying of the condensation fluid is repeated at least once.

9. A process according to claim 4, wherein the dampening by means of condensation as well as the subsequent drying of the condensation fluid is repeated at least once.

10. (cancelled)

11. A process according to claim 1, wherein dampening by means of condensation fluid is repeated at least once, without the phases of drying the condensation fluid in between dampening steps.

12. (cancelled)

13. A process according to claim 3, wherein dampening by means of condensation fluid is repeated at least once, without the phases of drying the condensation fluid in between dampening steps.

14. A process according to claim 4, wherein dampening by means of condensation fluid is repeated at least once, without the phases of drying the condensation fluid in between dampening steps.

15. (cancelled)

16. Apparatus for sterilizing surfaces of objects comprising:
means for generating a steam compound of water and hydrogen peroxide,
a sterilization chamber accommodating objects to be sterilized,
means for dampening surfaces of the objects in the sterilization chamber
by ~~condensing~~ abruptly releasing the steam compound into the sterilizing
chamber without additional transport gas flow being applied to the steam

compound, so that the steam compound becomes over-saturated and condenses in the shortest possible time on the surfaces, and

means for subsequently removing condensation fluid from the surfaces of the objects by drying carried out by evacuation of the sterilization chamber at a pressure below boiling points of water and hydrogen peroxide.

17. (cancelled)

18. Apparatus according to claim 16, wherein the means for generating a steam compound includes an evaporator chamber separate from the sterilization chamber, and

wherein means are provided for maintaining the pressure of the sterilization chamber lower than the pressure in the sterilization chamber.

19. Apparatus according to claim 18, wherein the means for dampening the surfaces include means for inducing flow of the steam compound from the evaporator chamber to the sterilization chamber by adiabatic expansion.

20. (cancelled)